

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.



The Delphion
Integrated
View

Other Views:
INPADOC

Title: **JP10279717A2: POROUS MEMBRANE AND SEPARATOR FOR BATTERY**
 ▶ Want to see a more descriptive title highlighting what's new about this invention?

Country: **JP Japan**
 Kind: **A**

Inventor(s): **NISHIYAMA SOJI**
YAMAMURA TAKASHI
MATSUSHITA KIICHIRO
WANO TAKASHI
KANEDA MITSUHIRO

Applicant/Assignee: **NITTO DENKO CORP**
News, Profiles, Stocks and More about this company



Issued/Filed Dates: **Oct. 20, 1998 / April 2, 1997**

Application Number: **JP1997000083676**

IPC Class: **C08J 9/00; H01M 2/16;**

Priority Number(s): **April 2, 1997 JP1997000083676**

Abstract:



Problem to be solved: To prepare a porous membrane having an improved pulling-out performance for a pin, consequently excellent in workability on the production of roll-type electric pole, imparting excellent charging and discharging characteristic and safety to a battery, and suitable as a separator of a non-aqueous electrolyte solution battery such as a lithium battery by compounding a thermoplastic resin with a lubricating agent in a specific small amount.

Solution: This porous membrane is obtained by compounding 100 pts.wt. of a thermoplastic resin such as polypropylene or polyethylene with 0.05-2 pts.wt. of a lubricating agent such as an aliphatic hydrocarbon, a fatty acid ester or fatty acid amide (e.g. paraffin wax, methyl stearate or palmitamide, respectively), in which the thermoplastic resin and the lubricating agent are noncompatible to each other.


COPYRIGHT: (C)1998,JPO

▶ See a clear and precise summary of the whole patent, in understandable terms.

Family: Show known family members

Other Abstract Info: **CHEMABS 129(25)331789F CAN129(25)331789F DERABS C99-005313**
DERC99-005313

Foreign References: **No patents reference this one**



[View
Image](#)

1 page



[Nominate this
for the Gallery...](#)

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)

© 1997 - 2002 Delphion Inc.



(19)

(11) Publication number: **10279717 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **09083676**(51) Intl. Cl.: **C08J 9/00 H01M 2/16**(22) Application date: **02.04.97**

(30) Priority:

(43) Date of application
publication: **20.10.98**(84) Designated contracting
states:(71) Applicant: **NITTO DENKO CORP**(72) Inventor: **NISHIYAMA SOJI
YAMAMURA TAKASHI
MATSUSHITA KIICHIRO
WANO TAKASHI
KANEDA MITSUHIRO**

(74) Representative:

**(54) POROUS MEMBRANE
AND SEPARATOR FOR
BATTERY**

(57) Abstract:

PROBLEM TO BE SOLVED: To prepare a porous membrane having an improved pulling-out performance for a pin, consequently excellent in workability on the production of roll-type electric pole, imparting excellent charging and discharging characteristic and safety to a battery, and suitable as a separator of a non-aqueous electrolyte solution battery such as a lithium battery by compounding a thermoplastic resin with a lubricating agent in a specific small amount.

SOLUTION: This porous membrane is obtained by compounding 100 pts.wt. of a thermoplastic resin such as polypropylene or polyethylene with 0.05-2 pts.wt. of a lubricating agent such as an aliphatic hydrocarbon, a fatty acid ester or fatty acid amide (e.g. paraffin wax, methyl stearate or palmitamide, respectively), in which the thermoplastic resin and the lubricating agent are noncompatible to

each other.

COPYRIGHT: (C)1998,JPO